

Fortron Strong D Fully Synthetic SAE 5W40 API SN/CF Dexos 2



Fortron Strong D Fully Synthetic SAE 5W40 API SN/CF Dexos 2

For Diesel, Diesel Common Rail

Approved formula designed to provide the ultimate protection for all technically-advanced passenger car and light commercial petrol and diesel engines. Specifically formulated for vehicles that require a fuel conserving 5W-40 low viscosity engine oil while at the same time needing enhanced protection during long oil drain intervals. Safe to use in modern diesel engines fitted with catalysts and Diesel Particulate Filters (DPF). These engines require an engine oil with a low Sulphated-Ash, Phosphorus and Sulphur content (Mid SAPS).



SUMMARY OF BENEFITS

- Optimum oxidation and thermal stability to minimize deposit formation
- Enhanced high temperature/high shear performance
- Inherent stay-in-grade shear stability
- Improved low temperature performance
- Potential fuel economy improvement

PERFORMANCE

- API SN/CF
- ACEA C3-12
- MB-Approval
226.5 / 229.31/229.51
- VM 502 00/505 01
- BMW Longlife-04
- Renault RN700/RN0710
- Porsche A40
- GM Dexos 2

Properties	UNIT	METHOD	5W-40
APPEARANCE	-	VISUAL	Bright & Clear
VISCOSITY 40° C	cSt	ASTM D445	94.45
VISCOSITY 100° C	cSt	ASTM D445	15.24
VISCOSITY INDEX	-	ASTM D2270	171
COLOR	-	ASTM D1500	L2.5
CCS @-30° C	cPs	ASTM D5293	6010
TOTAL BASE NUMBER	mgKOH/g	ASTM D2896	7.69

